

Professional Powered Speakers

EUROLIVE B315D/B312D

EUROLIVE D Series — 550-Watt 2-Way PA Speaker Systems with 15"/12" Woofer and 1.75" Titanium Compression Driver

- High-power 550-Watt 2-way PA sound reinforcement speaker system for live and playback applications
- Ultra-compact light weight system delivers excellent sound even at extreme sound pressure levels
- Revolutionary Class-D amplifier technology: enormous power, incredible sonic performance and super-light weight
- Internal switch-mode power supply for noise-free audio, superior transient response and very low power consumption
- Integrated sound processor for ultimate system control and speaker protection
- Extremely powerful long-excursion LF driver (B315D: 15" / B312D: 12") provides incredibly deep bass and acoustic power
- State-of-the-art 1.75" titanium-diaphragm compression driver for exceptional high-frequency reproduction
- Ultra-wide dispersion, large-format exponential horn
- Ultra-low noise Mic/Line input with Volume control and Clip LED
- Dedicated 2-band EQ for perfect sound adjustment
- Additional Line output allows linking of additional speaker systems



Finally, Setting Up for the Gig Just Got a Whole Lot Easier!

One of the coolest things about active loudspeakers is the lack of all the backbreaking racks of amps, crossovers and EQs that are often required to make passive systems sound almost as good. But that comes with a trade-off—that extra weight is transferred to the loudspeaker, making it difficult for a single user to heave all that mass onto a speaker stand.

By utilizing switch-mode power supplies and Class-D amplifier topology, the new EUROLIVE B315D and B312D loudspeakers provide more output power (800-Watts) and still weigh less than our best-selling B312A/B315A systems.

Sound quality is also improved, thanks to an integrated sound processor, which provides total system control, dependable protection of the transducers (woofer and tweeter) and virtually

eliminates distortion—even at extreme operating levels. In addition, both models feature an Ultra-Low Noise (ULN) MIC/LINE input with LEVEL control and a dedicated 2-band EQ (HIGH/LOW) for simple, yet effective tonal control.

What is Class-D Technology?

Instead of operating relatively continuously like Class AB circuits, Class-D amps switch on and off thousands of times per second, delivering power only when needed. In other words, the amplifier is either fully on or fully off, which significantly reduces power losses from the output devices given off as heat. Less heat means our amps don't need massive heat sinks, and that means we can make them lighter. Our no-compromise design means your EUROLIVE D Series loudspeakers will deliver full power with incredible fidelity all night long, without the need for lengthy rest cycles.

Continued on next page



EUROLIVE B315D/B312D

- Versatile trapezoidal enclosure design allows different positioning:
 - Stand mounting with 35 mm pole socket
 - Tilts on its side for use as a floor monitor
- Ergonomically shaped handles for easy carrying and setup
- High-quality components and exceptionally rugged construction ensure long life
- Conceived and designed by BEHRINGER Germany


When used in conjunction with switching-mode power supplies, which don't require huge and heavy transformers, our Class-D amplifiers provide tremendous dynamic punch and superior fidelity. The resulting speaker systems are much lighter, making them easy to transport and set up.

Processor-controlled Output


Dynamic processing is one of the best ways to maximize output without sacrificing sound quality.

The D Series' built-in circuitry automatically adjusts program content, allowing the loudspeaker to operate at extreme levels. It accomplishes this by reducing bass output slightly as you approach the limit of the transducers. This frees up LF (Low Frequency) amp and transducer resources, so that higher overall volume can be realized. It's like having a tiny soundman inside each cabinet constantly monitoring and tweaking output parameters.

Continued on next page



B315D/B312D rear panel callout



EUROLIVE B315D/B312D

Instant PA System

With just a single D Series loudspeaker and a microphone, you can set up an instant PA system—and you don't need an external mixer to do so! Thanks to the built-in mic preamp, you can connect any dynamic mic directly to the input and raise and lower the volume with the Level control. Just plug in the mic, place the speaker on a tabletop or standard speaker stand, and power up. It's that easy. And if you need more coverage, you can use the convenient LINK OUTPUT XLR connector to add more active loudspeakers.

Stereo Music System

You can even use a pair of D Series enclosures for stereo playback of your MP3, CD or old-skool cassette deck without any additional hardware. Just plug the appropriate stereo "breakout" adapter into your deck's output jack and run the cables to the 1/4" inputs on each loudspeaker. Set the Level and EQ controls the same on both enclosures. Voilà, instant party!

Monitor Mastery

Thanks to their trapezoidal design, D Series loudspeakers can be laid on their side to provide the ideal angle for onstage monitor wedge applications. Their extraordinary fidelity and frequency response make them a favorite of vocalists and instrumentalists alike. Hookup is simple, requiring only a single XLR or 1/4" cable



from the monitor send on your mixing console and, of course, power. Additional monitors can be chained together via the XLR LINK OUTPUT jack on the rear panel.


Custom-designed Transducers

While some of our competitors are content to buy ready-made transducers and plug them into their boxes, we custom-design and build


ours from scratch. Not only do we wind our own voice coils, we process the paper pulp into cones and machine every component that goes into them. This enables us to control the quality and make better components, like the long-excursion LF transducers and state-of-the-art 1.75" titanium drivers we deploy in each and every B315D and B312D enclosure.

Continued on next page


Connecting a Microphone



Connecting a Music Player



Connecting Multiple Loudspeakers



EUROLIVE B315D/B312D

Low Frequency Response

The EUROLIVE D Series was built with extended low frequency handling in mind. With a tuned port, internally braced, injection-molded enclosure, each model's custom-designed LF transducer really

cranks out tight low end. Keep in mind that bass response varies according to LF transducer size, so the larger the speaker, the more bass you will be able to generate.

PA Loudspeakers or Studio Monitors?

You'll love the sheer accuracy of these loudspeakers. More than a year went into the creation of the exponential horn/titanium-dome compression driver combination that not only does justice to loud rock and dance music, but also satisfies audiophiles with its musical timbre and attention to

detail. And for spoken word, singing or acoustic instruments, EUROLIVE D Series loudspeakers are unrivaled for their articulate and complex harmonic detail. In fact, many customers think it's the most natural-sounding speaker they've ever heard at anywhere near the price.

See your BEHRINGER dealer today for more information, which is also a good time to give the B315D and B312D a listening test—against the competition and against each other. Judge for yourself. And then own BEHRINGER with money to spare.

Specifications

B315D/B312D

System Data	
Low-frequency range	
RMS Power	280 W @ 8 Ω
Peak Power	450 W @ 8 Ω
High-frequency range	
RMS Power	65 W @ 8 Ω
Peak Power	100 W @ 8 Ω

B315D

Speaker Size	
Tweeter	1.75"/44 mm
Woofers	15"/387 mm

B312D

Speaker Size	
Tweeter	1.75"/44 mm
Woofers	12"/308 mm

B315D/B312D

Audio Inputs	
XLR (servo-balanced)	
Sensitivity	-40 dBu to +4 dBu
Input impedance	20 kΩ
¼" TRS (servo-balanced)	
Input impedance	20 kΩ

Level control	
Input Trim	-∞ to +30 dB
Max. input level	+22 dBu
Link Connector	XLR connector

B315D

Loudspeaker System Data	
Frequency Response	50 Hz to 18 kHz
Crossover frequency	1.8 kHz
Sound pressure level	max. 126 dB SPL @ 1m
Limiters	Optical
Dynamic Equalizer	Processor-controlled
Equalizer	
HIGH	12 kHz / ±15 dB
LOW	80 Hz / ±15 dB

B312D

Loudspeaker System Data	
Frequency Response	60 Hz to 18 kHz
Crossover frequency	2.1 kHz
Sound pressure level	max. 125 dB SPL @ 1m
Limiters	Optical
Dynamic Equalizer	Processor-controlled

Equalizer

HIGH	12 kHz / ±15 dB
LOW	80 Hz / ±15 dB

B315D/B312D

Power Supply

Voltage (Fuses)	
USA/Canada	120 V, 60 Hz (T 6.3 A H 250 V)
UK/Australia	240 V~, 50 Hz (T 3.15 A H 250 V)
Europe	230 V~, 50 Hz (T 3.15 A H 250 V)
Japan	100 V~, 50-60 Hz (T 6.3A H 250 V)
Power Consumption	max. 600 watts
Mains Connection	Standard IEC receptacle

B315D

Dimensions/Weight

Dimensions (H x W x D)	28.8 x 18.5 x 16.7" 732 x 470 x 424 mm
Weight	57.8 lbs / 26.2 kg

B312D

Dimensions/Weight

Dimensions (H x W x D)	25.9 x 15.5 x 15.1" 658 x 394 x 384 mm
Weight	49 lbs / 22.2 kg

Please note these specifications are preliminary and conceptual in nature, and as such are subject to change as product development progresses. This information is supplied for market research purposes only and is not to be made public in any manner. This document is solely the property of The MUSIC Group, or one of its subsidiaries, and must be surrendered upon request of the owner.

For service, support or more information contact the BEHRINGER location nearest you:

Europe MUSIC Group Services EU GmbH
Tel.: +49 2154 9206 4149 / Fax: +49 2154 9206 4199

USA/Canada MUSIC Group Services US Inc.
Tel.: +1 425 672 0816 / Fax: +1 425 673 7647

Singapore MUSIC Group Services SG (Pte.) Ltd
Tel.: +65 6845 1800 / Fax: +65 6214 0275

Australia MUSIC Group Services AU Pty Ltd
Tel.: +61 03 9877 7170 / Fax: +61 03 9877 7870

Japan MUSIC Group Services JP K.K.
Tel.: +81 3 5281 1180 / Fax: +81 3 5281 1181

TECHNICAL SPECIFICATIONS AND APPEARANCES ARE SUBJECT TO CHANGE WITHOUT NOTICE AND ACCURACY IS NOT GUARANTEED. BEHRINGER IS PART OF THE MUSIC GROUP (MUSIC-GROUP.COM). ALL TRADEMARKS ARE THE PROPERTY OF THEIR RESPECTIVE OWNERS. MUSIC GROUP ACCEPTS NO LIABILITY FOR ANY LOSS WHICH MAY BE SUFFERED BY ANY PERSON WHO RELIES EITHER WHOLLY OR IN PART UPON ANY DESCRIPTION, PHOTOGRAPH OR STATEMENT CONTAINED HEREIN. COLORS AND SPECIFICATIONS MAY VARY FROM ACTUAL PRODUCT. MUSIC GROUP PRODUCTS ARE SOLD THROUGH AUTHORIZED FULFILLERS AND RESELLERS ONLY. ALL RIGHTS RESERVED. © 2011 MUSIC Group IP Ltd, Trident Chambers, Wickhams Cay, P.O. Box 146, Road Town, Tortola, British Virgin Islands. 985-10000-00438